

OPTIMAAL DROGEN OP EEN BEPERKTE RUIMTE!



Mobile Rack, model B590

- Support length: 590 mm - Max. load capacity per support tube: 15 kg - Slot grids: 16 - Storeys: 16 - Spacing: 66 mm - Diameter of tubes: 23 mm - Diameter of castors: 125 mm <i>Detailed information on page 6</i>	Models	Length	Max. length	Depth	Height	Max. load capacity
	B590-VV	min. 550 mm	1,480 mm	790 mm	1,770 mm	200 kg/rack
	B590-2/2	1,510 mm	2,335 mm	730 mm	1,810 mm	200 kg/rack
	B590-X	min. 500 mm	1,500 mm	730 mm	1,810 mm	200 kg/rack
	B590-XX	min. 500 mm	3,000 mm	730 mm	1,810 mm	200 kg/rack
	B590-X3	min. 500 mm	3,000 mm	730 mm	1,810 mm	300 kg/rack

Mobile Rack, model B780

- Support length: 780 mm - Max. load capacity per support tube: 11 kg - Slot grids: 16 - Storeys: 16 - Spacing: 66 mm - Diameter of tubes: 23 mm - Diameter of castors: 125 mm <i>Detailed information on page 6</i>	Models	Length	Max. length	Depth	Height	Max. load capacity
	B780-VV	min. 550 mm	1,480 mm	980 mm	1,770 mm	200 kg/rack
	B780-2/2	1,510 mm	2,335 mm	920 mm	1,810 mm	320 kg/rack
	B780-X	min. 500 mm	1,500 mm	920 mm	1,810 mm	320 kg/rack

Mobile Rack, model C770

- Support length: 770 mm - Max. load capacity per support tube: 22 kg - Slot grids: 12 - Storeys: 12 - Spacing: 92 mm - Diameter of tubes: 29 mm - Diameter of castors: 160 mm <i>Detailed information on page 7</i>	Models	Length	Max. length	Depth	Height	Max. load capacity
	C770-2/2	1,510 mm	3,000 mm ⁹⁾	940 mm	1,840 mm	500 kg/rack
	C770-X	min. 500 mm	1,500 mm	940 mm	1,840 mm	500 kg/rack
	C770-XX	min. 500 mm	3,000 mm	940 mm	1,840 mm	500 kg/rack
	C770-X3	min. 500 mm	3,000 mm	940 mm	1,840 mm	750 kg/rack

Mobile Rack, model R660

- Support length: 660 mm - Max. load capacity per support tube: 28 kg - Slot grids: 31 - Storeys: 16 or 11⁵⁾ - Spacing: 66 mm or 113 mm¹¹⁾ - Diameter of tubes: 29 mm - Diameter of castors: 160 mm <i>Detailed information on page 8</i>	Models	Length	Max. length	Depth	Height	Max. load capacity
	R660-2/2	1,510 mm	3,000 mm ⁹⁾	830 mm	1,920 mm	500 kg/rack
	R660-X	min. 500 mm	1,600 mm	830 mm	1,920 mm	500 kg/rack
	R660-XX	min. 500 mm	3,200 mm	830 mm	1,920 mm	500 kg/rack
	R660-X3	min. 500 mm	3,200 mm	830 mm	1,920 mm	750 kg/rack

Mobile Rack, model R900

- Support length: 900 mm - Max. load capacity per support tube: 20 kg - Slot grids: 31 - Storeys: 11 or 16⁵⁾ - Spacing: 113 mm or 66 mm¹⁶⁾ - Diameter of tubes: 29 mm - Diameter of castors: 160 mm <i>Detailed information on page 8</i>	Models	Length	Max. length	Depth	Height	Max. load capacity
	R900-2/2	1,510 mm	3,000 mm ⁹⁾	1,060 mm	1,920 mm	500 kg/rack
	R900-X	min. 500 mm	1,600 mm	1,060 mm	1,920 mm	500 kg/rack
	R900-XX	min. 500 mm	3,200 mm	1,060 mm	1,920 mm	500 kg/rack
	R900-X3	min. 500 mm	3,200 mm	1,060 mm	1,920 mm	750 kg/rack

Subject to technical modifications.

All capacity data based on evenly distributed load, without shock loads.

⁹⁾ customised design

¹¹⁾ when fitted with 11 support tubes

¹⁶⁾ when fitted with 16 support tubes